



QUEST

Prod # 1340

Multilog 2000 Multi-gas Detector

The **Quest Multilog 2000** is a compact, personal, multi-gas monitor that simultaneously measures up to four gases from a selection of four toxic, oxygen and combustible gas sensors. Sturdy, lightweight, and easy to operate, this unit is ideal for a wide range of applications.

The Quest Multilog 2000 has a built-in datalogger capable of storing up to 78 hrs. of data at 1-minute sample intervals. Data can be stored continuously or at a preset trigger level and subsequently downloaded to the Questsuite program.

An external sampling pump may be used for remote sampling. Four readings are displayed at the same time on a large LCD.

Features:

- Smart sensors
- Accepts up to four toxic sensors
- Oxygen and/or combustible sensors
- RF-shielded case
- One button operation
- Data logging (78 hrs @ 1 minute intervals)
- Large, backlit LCD

Applications:

- Industrial hygiene monitoring
- Indoor air quality assessment
- Confined space entry
- General purpose safety monitoring

Accessories:

- **Standard**
 - Leather case
 - Battery charger
 - Hand aspirator
 - Belt clip
 - Shoulder harness
- **Optional**
 - Calibration adapter
 - Download cable

Specifications:

Ranges	: 0 to 30.0% (O ₂)
	: 0 to 999 ppm (CO)
	: 0 to 500 ppm(H ₂ S)
	: 0 to 50 ppm (SO ₂)
	: 0 to 50 ppm (NO ₂)
Resolution	: ± 0.1 (O ₂)
	: ± 1 ppm (CO)
	: ± 1 ppm (H ₂ S)
	: ± 0.1 ppm (SO ₂)
	: ± 0.1 ppm (NO ₂)
Dimensions	: 17.5 cm x 8.6 cm x 5.1 cm (6.9" x 3.4" x 2.0")
Weight	: 0.6 Kg (22 oz)
Display	: LCD with backlight
Alarm	: Audio / visual
Sensors	: Electrochemical (Toxic & Oxygen)
	: Catalytic (combustible)
Battery	: Rechargeable Ni-cad or 2 C alkaline
Battery life	: Ni-Cad (8 Hrs)
	: Alkaline (14 Hrs)
Operating temp	: -10°C to 40°C (14°F to 104°F)
Storage temperature	: -15°C to 60°C (5°F to 140°F)



**UL Listed - Class I,II,III, Division 1
Groups A, B, C, D, E, F and G.**

*Also Available for
Purchase. See last page
of catalog for details*