



HANNA

Prod # 5010

HI 9023C / 9024C / 9025C pH meter

The Hanna HI 9025C provides instant results in the most demanding field conditions. This unit is able to perform pH, ORP, ISE and temperature measurements for a long period of time without frequent battery changes. Automatic ranging and calibration make the unit extremely easy to use.

Specifications:

Range	: 0.00 to 14.00 pH : 0.0 to + 399.9 mV(ISE) : 0.0 to + 1999 mV(ORP) : 0.0 to 100.0°C
Accuracy	: ± 0.01 pH, ± 0.1 mV ISE, ± 1 mV (ORP), ± 0.4 °C
Construction	: ABS plastic-waterproof
Display	: LCD
Calibration	: Automatic with 3 memorized buffers
Temp. Compensation	: Automatic or Manual from 0°C - 100°C
Operating Conditions	: 0°C - 50°C, 100% RH
Battery	: 4 x AAA alkaline
Battery life	: 70 hrs
Dimensions	: 19.6 cm x 8.0 cm x 6.0 cm : (7.7" x 3.1" x 2.4") : Probe 12.0 cm x 1.2 cm (dia)
Weight	: 425 g (15 oz.)

Features:

- Water-proof housing
- Large liquid crystal display
- 0.1 mV resolution
- Automatic buffer recognition
- Long battery life

Application:

- Water testing

Standard Accessories:

- pH electrode
- Temperature probe
- Carrying case

Optional

- Model 9024 pH meter without ISE/ORP



*Also Available for
Purchase. See last page
of catalog for details*