

# HI 93703C Turbidity Meter



Prod # 5016



The **HI 93703 Turbidity Meter** provides lab-grade accuracy of turbidity measurements in a portable field instrument.

The HI 93703 is very simple to use and has only 4 keys. The meter is programmed to store and retrieve the last calibration time and date to assure adherence to established procedures.

## Features:

- Portable
- Large LCD
- Dual measurement scale
- Automatic calibration
- Assists with GLP  
(Good Laboratory Practice)

## Specifications:

Range	: 0.00 to 50.00 FTU : 50 to 1,000 FTU
Resolution	: 0.01 and 1 FTU
Accuracy	: $\pm 5\%$ or $\pm 0.5$ FTU
Display	: 7 line, 16 character LCD
Operating Conditions	: $0^{\circ}\text{C}$ to $50^{\circ}\text{C}$ , 0-95% RH
Battery	: 4 x AA alkaline batteries
Battery life	: 40 hrs
Dimensions	: 22.0 cm x 8.2 cm x 6.6 cm ( 8.7" x 3.2" 2.6" )
Weight	: 510 g ( 18 oz )

## Typical Applications:

- Municipal waste water
- Drinking water
- Water conditioning
- Beverage processing
- Food industry

## Accessories:

- Case
- Cuvets

*Also Available for  
Purchase. See last page  
of catalog for details*