



### ***Features:***

- Built-in rotameter
- Long battery life
- Timer
- RFI & EMI shielded

### ***Applications:***

- Industrial hygiene personal testing
- Area sampling
- Indoor Air Quality testing

The SKC Universal Sample Pump is ideal for a broad range of applications for industrial hygiene studies, environmental sampling and indoor air quality assessments.

The SKC 224-PCXR4 can be used as a “personal”, “area”, or “fence-line” pump that can be connected to sampling media such as filters, impingers, sorbent pads, tubes and sample bags.

## *SKC 224-PCXR4 Air Sampling Pump*

### *Specifications:*

Dimensions	: 4.8 cm x 11.9 cm x 13.0 cm : (1.9" x 4.7" x 5.1")
Weight	: 964 g (32 oz)
Operating range	: 5-5000 ml/min : 5 to 500 ml/min with low flow adapter
Operating temperature	: -20°C - 45°C
Flow control	: $\pm 5\%$ of set point
Battery life	: 8 hrs

UL Approved - Class I, Groups A,B,C & D Class II Groups E,F,G & Class III

### *Standard Accessories (included):*

- Battery Charger (single or multi)
- Tubing
- Screwdriver

### *Optional Accessories:*

- Low flow adapters
- Cassette holders
- Tube holders
- Cyclones (for respirable dust sampling)

### *Consumables:*

- Tedlar bags
- Sorbent tubes
- Sampling cassette
- Asbestos sampling media
- Mould sampling media