



This rugged, water-proof **Conductivity Meter** provides instant field results in any weather. All conductivity readings, from de-ionized water to brine, are generated by the sturdy, 4-ring potentiometric probe and do not require recalibration.

### *Features:*

- Water-resistant housing
- 4 ranges of measurements with just one probe
- 4-ring potentiometric method
- Battery error prevention system

### *Applications:*

- Groundwater testing

## *HANNA HI 9033 Conductivity Meter*

### *Specifications:*

Ranges	: 0.0 to 199.9 $\mu\text{S}/\text{cm}$ : 0 to 1999 $\mu\text{S}/\text{cm}$ : 0.00 to 19.99 $\text{mS}/\text{cm}$ : 0.0 to 199.9 $\text{mS}/\text{cm}$
Accuracy	: $\pm 1\%$ Full scale
Temp. compensation	: Automatic from 10°C to +50°C
Display	: LCD
Operating Conditions	: 0°C to 50°C, 100% RH
Battery	: 9V alkaline
Battery life	: 75 hrs
Dimensions	: 19.6 cm x 8.0 cm x 6.0 cm (7.7" x 3.1" x 2.4")
Weight	: 0.425 kg (15 oz)

### *Standard Accessories (included):*

- Distilled water
- Calibration solution
- Extra batteries